


For Use With 1 1/2" Fire Hose Rack Assembly & 2 1/2" Fire Dept. Valve



1200 Series

Series 1200 cabinets will accommodate a single 1 1/2" or 2 1/2" Fire Hose Rack assembly Fire Dept Valve with cap and chain.

STANDARD EQUIPMENT

- * Heavy gauge steel construction tub, door and trim
- * White powder coat finish
- * Continuous steel piano hinge
- * Pull handle with roller catch

CABINET OPTIONS

- * Prefix **FR** for Fire Rated Cabinet
- * Suffix **AL** for clear anodized aluminum door and frame
- * Suffix **SS** for Stainless Steel # 4 finish door and frame
- * Suffix **FF** for Detention Grade Heavy Steel Door And Trim
- * Door Styles See page 2-5
- * Other cabinet options See page 2-7, 2-19 and 2-20

ORDERING PROCEDURE

- * Select cabinet Figure No.
- * Select door style
- * Select type of hose rack assembly (Refer to Section 3000)
- * Select Fire Dept Valve with Cap and chain (Refer to Section 5000)
- * Select Cabinet Options

Fig. No.	Trim Style	Trim Proj. Tp.	Valve Cap.	Hose Cap.	Inside box dimensions			Overall Outside dim		Knockout locations				Wall Opening Required			FIRE RATED CABINETS Wall Opening Required FR Option		
					A	B	C	D	E	J	K	M	N	Width	Height	Depth	Width	Height	Depth
1200	Recessed	3/8"	1 1/2"	75'	24	38 3/4	8	27 3/8	42 1/8	4	2 1/2	4	4	25	39 3/4	7 3/4	26	40 7/8	8 5/8
1201	Semi-	1 1/4"		Poly	24	38 3/4	8	27 3/8	42 1/8	4	2 1/2	4	4	25	39 3/4	6 7/8	26	40 7/8	7 3/4
1202	Recessed	2 1/2"	or	50'	24	38 3/4	8	27 3/8	42 1/8	4	2 1/2	4	4	25	39 3/4	5 3/8	26	40 7/8	6 1/2
1206	Trimless		2 1/2"	SJRL	24	38 3/4	8	24 1/4	39	4	4	4	4	24 1/2	39 1/4	8 1/4			
1208	Surface			Hose	27 3/16	41 15/16	8 1/2	27 3/8	42 1/8	a	a	a	a						
1210	Recessed	3/8"	1 1/2"	100'	32 3/4	38 3/4	8	36 1/8	42 1/8	4	2 1/2	4	4	33 3/4	39 3/4	7 3/4	35	40 7/8	8 5/8
1211	Semi-	1 1/4"		Poly	32 3/4	38 3/4	8	36 1/8	42 1/8	4	2 1/2	4	4	33 3/4	39 3/4	6 7/8	35	40 7/8	7 3/4
1212	Recessed	2 1/2"	or	75'	32 3/4	38 3/4	8	36 1/8	42 1/8	4	2 1/2	4	4	33 3/4	39 3/4	5 5/8	35	40 7/8	6 1/2
1216	Trimless		2 1/2"	SJRL	32 3/4	38 3/4	8	33	39	4	4	4	4	33 1/4	39 1/4	8 1/4			
1218	Surface			Hose	35 15/16	41 15/16	8 1/2	36 1/8	42 1/8	a	a	a	a						

a- No knockouts provided unless specified on surface mounted cabinets

Note: Add 5/8" to depth of wall opening required for cabinets with aluminum frame

9" Tub option available upon request on 1200 and 1210 Series

NOTE: FIRE RATED CABINETS HAVE NO KNOCKOUTS

