


## For Use With Fire Dept Valve

Series 1700 and 1720 cabinets will accommodate a single 1 1/2" or 2 1/2" with Fire Dept. Valve with Cap and Chain



1700 Series

### STANDARD EQUIPMENT

- \* Heavy gauge steel construction tub, door and trim
- \* White powder coat finish
- \* Continuous steel piano hinge
- \* Pull handle with roller catch

### CABINET OPTIONS

- \* Prefix **FR** for Fire Rated Cabinet
- \* Suffix **AL** for clear anodized aluminum door and frame
- \* Suffix **SS** for Stainless Steel # 4 finish door and frame
- \* Suffix **FF** for Detention Grade Heavy Steel Door And Trim
- \* Door Styles See page 2-5
- \* Other cabinet options See page 2-7, 2-19 and 2-20

### ORDERING PROCEDURE

- \* Select cabinet Figure No.
- \* Select door style
- \* Select Fire Dept Valve with Cap and Chain (Refer to Section 5000)
- \* Select cabinet Options

Fig. No.	Trim Style	Trim Proj Tp.	Valve Cap.	Inside box dimensions			Overall Outside dim		Knockout locations		Wall Opening Required			FIRE RATED CABINETS Wall Opening		
				A	B	C	D	E	J	K	Width	Height	Depth	Width	Height	Option Depth
1700	Recessed	3/8"		18	18	8	21 3/8	21 3/8	9	4	19	19	7 3/4	20	20 1/8	8 5/8
1701	Semi-recessed	1 1/4"		18	18	8	21 3/8	21 3/8	9	4	19	19	6 7/8	20	20 1/8	7 3/4
1702	recessed	2 1/2"	1 1/2"	18	18	8	21 3/8	21 3/8	9	4	19	19	5 5/8	20	20 1/8	6 1/2
1706	Trimless		or	18	18	8	18 1/4	18 1/4	9	4	18 1/2	18 1/2	8 1/4			
1708	Surface		2 1/2"	21 3/16	21 3/16	8 1/2"	21 3/8	21 3/8	a	a						
1710	Recessed	3/8"		18	18	10	21 3/8	21 3/8	9	5	19	19	9 3/4	20	20 1/8	10 5/8
1711	Semi-recessed	1 1/4"	1 1/2"	18	18	10	21 3/8	21 3/8	9	5	19	19	8 7/8	20	20 1/8	9 3/4
1712	recessed	2 1/2"	or	18	18	10	21 3/8	21 3/8	9	5	19	19	7 5/8	20	20 1/8	8 1/2
1716	Trimless		2 1/2"	18	18	10	18 1/4	18 1/4	9	5	18 1/2	18 1/2	10 1/4			
1718	Surface			21 3/16	21 3/16	10 1/2"	21 3/8	21 3/8	a	a						
1720	Recessed	3/8"		26	26	10	29 3/8	29 3/8	13	5	27	27	9 3/4	28	28 1/8	10 5/8
1721	Semi-recessed	1 1/4"	1 1/2"	26	26	10	29 3/8	29 3/8	13	5	27	27	8 7/8	28	28 1/8	9 3/4
1722	recessed	2 1/2"	or	26	26	10	29 3/8	29 3/8	13	5	27	27	7 5/8	28	28 1/8	8 1/2
1726	Trimless		2 1/2"	26	26	10	26 1/4	26 1/4	13	5	26 1/2	26 1/2	10 1/4			
1728	Surface			29 3/16	29 3/16	10 1/2"	29 3/8	29 3/8	a	a						

a- No knockouts provided unless specified on surface mounted cabinets

Note: Add 5/8" to depth of wall opening required for cabinets with aluminum frame

Note: If 2 1/2" x 1 1/2" reducing adapter is used for Fire Dept Valve "C" dimension should be no less than 10".

\* Trimless, recessed and semi-recessed cabinets furnished with combination knockouts (1 1/2" and 2 1/2" on both sides)

NOTE: FIRE RATED CABINETS HAVE NO KNOCKOUTS

