



Figure No. 4202

WATER 2 1/2 GALLON

**U/L LISTED
STANDARD EQUIPMENT:**

Water a liquid agent only recommended for fighting Class "A" fires in hand portable extinguishers.

IDEAL USES:

Schools, theaters, department and retail store rooms.

WATER MIST 2 1/2 GALLON

**U/L LISTED
STANDARD EQUIPMENT:**

Distilled water extinguishing agent. White Painted finish.

IDEAL USES:

Hospitals, Health Care Facility and Clean Rooms



Figure No. 4206

Figure No.	U/L Rating	Capacity (gallons)	Height	Width	Depth (dia.)	Range of Sream	Valve Material	Cylinder Material	Bracket	Shipping Weight (lbs.)
4202	2A	2 1/2	24 1/2"	9"	7"	40-55'	Brass	Stainless Steel	Wall	7 1/2 Lbs.
4206	2A:C	2 1/2	24 1/2"	11"	7"	10-12'	Brass	Painted Steel	Wall	8 Lbs.



Figure No. 4305

REGULAR BC

Regular BC

Series 4300

U/L LISTED

STANDARD EQUIPMENT:

Sodium Bicarbonate based dry agent capable of fighting Class "B" and "C" type fires.

IDEAL USES:

Kitchens, garages, vehicles and boats.



Figure No. 4310

Figure No.	U/L Rating	Capacity (lbs.)	Height	Width	Depth (dia.)	Range of Sream	Valve Material	Cylinder Material	Coast Guard Approved	Bracket	Shipping Weight (lbs.)
4302	10B:C	2 1/2	15 1/2"	5 3/4"	3"	9-15'	Alum.	Steel	Yes	V/M	5 1/2 Lbs.
4305	40B:C	5	15 1/2"	5 1/2"	4 1/4"	12-18'	Alum.	Steel	Yes	V/M	9 1/4 Lbs.
4310	40B:C	10	20"	7 3/4"	5"	15-21'	Alum.	Steel	Yes	Wall	18 Lbs.
4320	120B:C	20	23 1/4"	10 3/4"	7"	15-21'	Alum.	Alum.	Yes	Wall	38 Lbs.