

DRY CHEMICAL * ABC

MULTIPURPOSE ABC- SERIES 4000
U/L LISTED

STANDARD EQUIPMENT:
Heavy duty steel cylinder with red enamel except for 4004 (Alum. Cylinder)
Rugged metal valves and siphon tubes monoammonium phosphate based.

IDEAL USES:
Home office buildings, warehouses, and wood working areas. (Not recommended for delicate computers)



Figure No. 4005

Figure No. 4010

Figure No.	U/L Rating	Capacity (lbs.)	Height	Width	Depth (dia.)	Range of Sream	Valve Material	Cylinder Material	Coast Guard Approved	Bracket	Shipping Weight (lbs.)
4002	1A:10B:C	2 1/2	15 1/2"	5 3/4"	3"	9-15'	Alum.	Steel	Yes	V/M	5 1/2 Lbs.
4005	2A:10B:C	5	15 1/4"	7 1/4"	4 1/4"	12-18'	Alum.	Steel	Yes	Wall	9 1/2 Lbs.
4007	3A:40B:C	5	15 1/4"	7 1/4"	4 1/4"	12-18'	Alum.	Steel	Yes	Wall	9 1/2 Lbs.
4008	3A:40B:C	6	16"	7 3/4"	5"	15-21'	Alum.	Steel	Yes	V/M	12 3/4 Lbs.
4010	4A:80B:C	10	20"	7 3/4"	5"	15-21'	Alum.	Steel	Yes	Wall	18 Lbs.
4020	10A:120B:C	20	23 1/4"	10 1/4"	7"	15-21'	Alum.	Steel	Yes	Wall	38 Lbs.

HALOTRON I

STORED PRESSURE FIRE- EXT SERIES 4100
U/L LISTED

STANDARD EQUIPMENT:
HydroChloroFluoro Carbon non-conductive agent pressurized with Argon.
Approved by EPA & FAA as HCFC Blend B for use with Class ABC fires.

IDEAL USES:
Computers, telephones, sensitive data storage areas, office and aircraft flights.



Figure No. 4132

Figure No. 4139

Figure No.	U/L Rating	Capacity (lbs.)	Height	Width	Depth (dia.)	Range of Sream	Valve Material	Cylinder Material	Coast Guard Approved	Bracket	Shipping Weight (lbs.)
4132	2B:C	2 1/2	15 1/2"	6 3/8"	3"	6-10'	Alum.	Steel	No	V/M	5 1/4 Lbs.
4135	5B:C	5	15 1/4"	5 3/4"	4 1/4"	9-15'	Alum.	Steel	No	V/M	9 1/2Lbs.
4137	1A:10:BC	11	21 7/8"	9 1/4"	6"	9-15'	Alum.	Steel	Yes	Wall	22Lbs.
4139	2A:10:BC	15 1/2	21 7/8"	9 1/4"	6"	12-18'	Alum.	Steel	Yes	Wall	22 Lbs.