

SINGLE INLET



Figure No. 6341

An inlet connection with 250 G.P.M. minimum inlet capacity to supplement the fire protection water supply. Provides unobstructed water supply. Flush round design enhances appearance and provides unobstructed passage.

STANDARD EQUIPMENT: Cast Brass round plate with double female adapter; plug and chain; branding as selected.
SPECIFY THREAD AND BRANDING.

BRANDING: "Standpipe", "Auto Spkr."

FINISH: Cast Brass

OPTIONAL FINISH: PB-Polished Brass
 PC-Polished Chrome



Figure No. 6342

| Round Plate | |
|-------------|---------------|
| Figure No. | Size |
| 6341 | 2 1/2 X 2 1/2 |
| 6342 | 3 X 2 1/2 |
| 6343 | 3 X 3 |

RESIDENTIAL FIRE DEPT. CONNECTION



Figure No. 6345

An inlet connection to supplement the water supply to a residential sprinkler system.

STANDARD EQUIPMENT: 1 1/2" cast brass round plate assembly with integral pin lug swivel inlet. Hose thread inlet swivel, 1 1/2" NPT female outlet on back of plate. Cast brass plug and brass chain. Overall outside Diameter 4 3/8".

SPECIFY THREAD AND BRANDING.
U/L LISTED.

BRANDING: "Auto Spkr."

FINISH: Cast Brass

OPTIONAL FINISH: PB-Polished Brass
 PC-Polished Chrome