

SINGLE WATERWAY MONITOR



Figure No. 9004

Fixed installation for one man operation where high gallonages are required. Intended for permanent, stationary protection of high risk areas.

STANDARD EQUIPMENT: Red painted brass body. Positive locking control. Pressure gun grease fitting. Full 360 degree horizontal traverse.

NOZZLE NOT INCLUDED. SEE PAGE 9-6.

Figure No. 9004

Fig. No.	Operated	Material	G.P.M.	Outlet	Base Options
9004	Worm Gear	Brass	1250	2 1/2"	3" NPT Female 3" or 4" Flange

HANDLE OPERATED MONITORS



Figure No. 9006

Fixed installation for one man operation where high gallonages are required. Intended for permanent, stationary protection of high risk areas.

STANDARD EQUIPMENT: All brass construction with stainless steel and brass twist locking mechanism. Stainless steel handle rod. Grease fittings on lower swivels. Red enamel finish. Full 360 degree horizontal traverse.

NOZZLE NOT INCLUDED. SEE PAGE 9-6.

Figure No. 9006

Fig. No.	Operated	Material	G.P.M.	Outlet	Base Options
9006	Handle	Brass	750	2 1/2"	2 1/2", 3" 4" Female NPT Flange 125-150ASA 2 1/2, 3", 4", 6" Flange 250-300ASA 2 1/2", 3", 4"