

SINGLE WATERWAY MONITORS




Figure No. 9025

Figure No. 9025-9027

Fixed installation for one man operation required. Intended for permanent, stationary protection of High risk areas - greater range because of reduced friction loss.

STANDARD EQUIPMENT: Red painted finish. **NOZZLES NOT INCLUDED. SEE PAGE 9-6.**



Figure No. 9027

Fig. No.	Material	G.P.M.	Waterway	Outlet	Base Options
9025	Brass	1000	3.0"	2 1/2"	3" Fe NPT 3"-4" 150# ANSI FLANGE
9027	Aluminum	1000	3.0"	2 1/2"	3" Inlet- 150# flange

SINGLE WATERWAY MONITORS



Figure No. 9031

Figure No. 9031-9033-9035

Fixed installation for one man operation required. Intended for permanent, stationary protection of High risk areas - greater range because of reduced friction loss.

STANDARD EQUIPMENT: All brass construction with stainless steel and brass twist locking mechanism. Stainless steel handle rod. Grease fittings on lower swivels. 2 1/2" NST outlet. Full 360 Degree rotation. **NOZZLE NOT INCLUDED. SEE PAGE 9-6.**



Figure No. 9033

Fig. No.	Material	G.P.M.	Waterway	Outlet	Base Options
9031	Brass	1250	3"	2 1/2"	3" Female NPT Flange 150 ANSI 2 1/2", 3", 4", 6"
9033	Chrome	1250	2 1/2"	2 1/2"	2 1/2", 3", 4" Female NPT Flange 150 ANSI 2 1/2", 3", 4"
9035	Stainless Steel	2500	3"	3 1/2"	3", 4" Female NPT Flange 150 ANSI 4"